



revolabs

Solo™

Executive



4 OR 8 CHANNEL WIRELESS MICROPHONE SYSTEM

FOR EXECUTIVE BOARDROOMS AND LARGE CONFERENCE ROOMS

The Revolabs Solo™ Executive 4 or 8 channel Wireless Microphone System is the **ideal audio conferencing solution for large conference rooms and boardrooms**. Solo allows up to eight wireless microphones for audio capture in these larger rooms. When combining two systems in North America, or up to three systems in international markets, **up to 16 or 24 wireless microphones can be combined** to capture audio in one room, respectively.

Revolabs Solo Executive supports audio from 100 – 6,800 Hz, capturing the main frequencies used in human speech. Flexibility of the wireless microphones allows for placement close to participants without requiring wiring or custom installation. Multipurpose rooms in which configurations are changed regularly improved audio capture is essential, such as **training or conference rooms**.

The Revolabs Solo Executive system is built to work with the existing AV equipment installed in conference rooms. The microphone output can be connected to mixers and audio controllers, making the audio available for audio and video conferencing equipment in the conference room. Room control systems can also be integrated to the Solo Executive system to

control each microphone in the installation.

All wireless communication between the microphones and receiver is digitally encrypted using **128-bit encryption technology**, securing the communication and preventing unwanted listeners.

With **four different microphone types**, the Revolabs Solo Executive allows users to mix and match the microphone types to best suit the audio needs of the room. The omni-directional tabletop microphone allows for 360-degree coverage around the microphone, ideal for a conference table. The directional tabletop microphone enables voice capture of two or three people, perfect for training rooms or panel discussions. The wearable, lapel microphone is ideal for presenters who need a microphone to capture their voice audio. Finally, the XLR microphone adapter gives users an option of using a handheld microphone wirelessly with the Solo Executive system.

Rechargeable batteries for the Revolabs Solo microphones provide **up to eight hours of talk time** with a two-hour recharge time. With the Revolabs Solo wireless solution, **enterprise users can finally move around their conference room, and be heard!**

BENEFITS

Superior Audio Quality

Wideband frequency response provides audio delivering spoken word clarity

Wireless Freedom

Lets users sit anywhere within a conference room or walk around freely

Support for Multiple Microphones

Wearable, tabletop boundary and handheld

No More Cell Phone Buzz

RF Armor™ technology lets microphones operate “buzz” free when in direct contact with other wireless electronic devices

Secure

128-bit encryption prevents unwanted listeners from listening in





Revolabs Solo™ Executive 4 or 8 Channel Wireless Microphone System

AUDIO	Channels	4 or 8 channels per system 16 channels maximum (2 systems) North America 24 channels maximum (3 systems) International
	Radio Frequency	North and South America: 1920 to 1930 MHz and 315 MHz (System Mute North America) International: 1880 to 1900 MHz (DECT EU) and 433.92 MHz (System Mute)
	Range	100 feet (30 meters) approx. (no obstructions) Out-of-range alarm
	Bandwidth	100-6,800 Hz
BASE STATION	Power	100-240V, 50-60 Hz, 20W IEC Universal power connector
	Connectors/Interfaces	Channel LED indicators Pairing Push Buttons BUS configuration switch 3.5 mm Mini phoenix line level inputs and line level outputs per channel 3.5 Mini Phoenix serial bus
CHARGER BASE	Power	5V DC, 2A 100-240V, 50-60 Hz; Power supply included
	Connectors/Interfaces	4 or 8 proprietary 4 pin microphone charge jacks Master mute control button
MICROPHONES	Battery	Lithium Polymer
	Talk Time	Up to 8 hours
	Charge Time	2 hours
	Encryption	128-bit proprietary (per microphone channel)
	RF Shield	No cell phone interference due to RF Armor™ technology
	Mute Button	For muting and pairing
	LED Indicator	For mute status, pairing, and battery charge
	Audio Out Port	2.5 mm Mono headphone jack
	Power/Charging Port	Revolabs proprietary 4 pin
	Connector	3 pin XLR Female for use with dynamic microphones only (XLR Adapter)

HEAR EVERY WORD



Revolabs HQ
144 North Road
Sudbury, MA 01776
USA
800-326-1088

Revolabs EMEA
+33-1-6459-8904

Revolabs APAC
+852-92297743

Revolabs India-Middle East
+91-124-4711630

info@revolabs.com
www.revolabs.com